

Product Information Sheet H15 12V

GENERAL					
	H15 12V 15W/55W PGJ23t-1		Features	original equipment manufacturer quality, hardglass, UV-cut	
	Ordering Number 28070		Standard	ECE R37 DOT	
Product Description	halogen headlighting lamp		Typical Applications	high beam, daytime running light	
TECHNICAL DETAILS					
1	reference axis		Rated Voltage	ECE R37: 12V	
			Rated Wattage	max. 19W/64W @13,2V	
55 max.			Base	PGJ23t-1	
0- 06			Operating Conditions	burning position: horizontal	

Geometry

Light center length: 30mm +0,35mm/-0,25mm Bulb diameter: max. 17mm

Rated Wattage	max. 19W/64W @13,2V		
Base	PGJ23t-1		
Operating Conditions	burning position: horizontal		
Luminous Flux	260/1350 lm ± 10% @13,2V		
Lifetime	B3: 250/2000h HB/(DRL/PL) @13,2V Tc: 500/4000h HB/(DRL/PL) @13,2V		

DELIVERY DETAILS

Packaging

Industrial Packaging: 144pcs. (4×36) Commercial Box Packaging: 100pcs. (10×10×1) Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.

valid from 07.12.2017 replace for 12.04.2017 file 28070 - H15 12V 15W/55W PGJ23t-1.101