ത

Œ

 $(\mathbb{C}$

S

ł

0

 \bigcirc

0

STERLING HINGES

Heavy Duty Friction Hinges for Commercial Applications

Designed to give superior window balancing, the Sterling range of hinges offer good durability and weather sealing combined with excellent weight carrying for curtain walling applications.

- Easy to fit with adjustable friction mechanism
- Asymmetric location system for reliable, accurate closure
- Improved weather sealing and draught proofing performance from asymmetric vent arm form
- Long and reliable working life tested to operate for 30,000 cycles
- Manufactured from high grade Austenitic stainless steel
- Suitable for vents from 0.3m to 2.5m high, up to 180 kg in weight
- Self balancing eliminates the need for additional support arms
- Composite steel/plastic slider for strength, durability and smooth operation
- Available in 10" to 26" top hung, 10" and 16" side hung
- 10" and 16" side hung open to around 90° for easy cleaning of windows
- Easy to use, adjustable opening stop on all top hung versions
- Optional hinge position adjustment device available separately



It is the responsibility of the user to ensure that this document is at the latest issue.

Due to our policy of continual product improvement we reserve the right to alter specifications without notice.

It is the responsibility of the window manufacturer to ensure that the finished window meets the required performance and safety specification.

© SECURISTYLE LTD 2006

Securistyle Ltd. Kingsmead Industrial Estate Princess Elizabeth Way, Cheltenham, Gloucestershire, GL51 7RE Tel: +44 (0) 1242 221200 Fax: +44 (0) 1242 520828 Web: www.securistyle.co.uk